

CAT LADDER



MAX.WORKING PRESSURE 10 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS

MOUNTING POSITION VERTICAL V

R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Top Ga	Pip Or Se	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
CLA508-8	800	530	30	E/H/D	3	8	946	277	300	400		
CLA510-10	1030	530	30	E/H/D	4	10	1185	347	400	400		
CLA513-12	1260	530	30	E/H/D	5	12	1421	416	400	600		
CLA515-14	1490	530	30	E/H/D	6	14	1657	485	600	900		
CLA517-16	1720	530	30	E/H/D	7	16	1892	554	900	900		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



