

CENGIZ



MAX.WORKING PRESSURE 10 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS

MOUNTING POSITION VERTICAL V

R Radiator / RT Radiator & Heated Towel Rail / T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipe Or Sec	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
CEN5C7	690	500	60	E/H/D	2	9	876	257	300	400		
CEN5C11	1100	500	60	E/H/D	3	14	1323	388	400	600		
CEN5C17	1650	500	60	E/H/D	4	21	1985	582	900	900		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



