

CLIPPER



MAX.WORKING PRESSURE 10 Bar
MAX.WORKING TEMPERATURE 95°C
OPEN/CLOSED HEATING SYSTEM O-C
MATERIAL STAINLESS STEEL SS
MOUNTING POSITION VERTICAL V
R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator
 Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems
 Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Top Gap	Pipe Or	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
CL1505	1500	220	130	H	5	5	1728	506	H : Central Heating Only			
CL1507	1500	310	130	E/H/D	7	7	2418	708	340	400		
CL1509	1500	400	130	E/H/D	9	9	3118	913	340	400		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



