

# COMBE



**MAX.WORKING PRESSURE 10 Bar**

**MAX.WORKING TEMPERATURE 95°C**

**OPEN/CLOSED HEATING SYSTEM O-C**

**MATERIAL STAINLESS STEEL SS / MILD STEEL MS**

**MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS**

**R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator**

**Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems**

**Finish S : Brushed Matt / P : Polished**

Model Name	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipes Or Section	Heat Output Delta T 50 C		E :Electric only		Brushed Matt - S	Polished P
							BTU	Watts	Choice of Elements Watts			
COM10-R(S,P)	920	500	80	E/H/D	2	12	3197	<b>936</b>	400	600		
COM10-L(S,P)	920	500	80	E/H/D	2	12	3197	<b>936</b>	400	600		
COM15-R(S,P)	1460	500	80	E/H/D	3	20	5328	<b>1560</b>	600	900		
COM15-L(S,P)	1460	500	80	E/H/D	3	20	5328	<b>1560</b>	600	900		
COM18-R(S,P)	1710	500	80	E/H/D	4	25	6660	<b>1950</b>	600	900		
COM18-L(S,P)	1710	500	80	E/H/D	4	25	6660	<b>1950</b>	600	900		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

