

ELIXIR



MAX.WORKING PRESSURE 10 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS / MILD STEEL MS

MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS

R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Pipes or Sections	Heat Output Delta T 50 C		E :Electric only		Brushed Matt - S	
						BTU	Watts	Choice of Elements Watts			
ELX120 (S)	900	1200	255	H	30	11190	3277	2x600	2x900		
ELX150 (S)	900	1500	255	H	30	12425	3638	2x600	2x900		
ELXM120 (S)	630	840	60	-	-	-	-				
ELXM150 (S)	630	1050	60	-	-	-	-				
ELXGS120 (S)	100	840	60	-	-	-	-				
ELXGS150 (S)	100	1050	60	-	-	-	-				

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

