

FATIH



MAX.WORKING PRESSURE 10 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS / MILD STEEL MS

MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS

R Radiator/ RT Radiator & Heated Towel Rail/ **T Heated Towel Rail / TR Heated Towel Rail & Radiator**

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipes or Sections	Heat Output Delta T 50 C		E :Electric only		Brushed Matt - S	Polished P
							BTU	Watts	Choice of Elements Watts			
FA5F8(S,P)	830	500	90	E/H/D	3	14	1527	447	300	400		
FA5F11(S,P)	1110	500	90	E/H/D	4	18	2012	589	400	600		
FA5F17(S,P)	1670	500	90	E/H/D	6	26	3019	884	600	900		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

