

# GRANDEUR



**MAX.WORKING PRESSURE 10 Bar**

**MAX.WORKING TEMPERATURE 95°C**

**OPEN/CLOSED HEATING SYSTEM O-C**

**MATERIAL STAINLESS STEEL SS / MILD STEEL MS**

**MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS**

**R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator**

**Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems**

**Finish S : Brushed Matt / P : Polished**

Model Name	Height mm	Length mm	Dept mm	Fuel Options E/H/D	Pipes or Sections	Heat Output Delta T 50 C		E :Electric only		
						BTU	Watts	Choice of Elements Watts	Brushed Matt - S	Polished P
GRA106(S,P)	660	965	210	H	26	4317	<b>1264</b>	H:Central Heating Only		
GRA126(S,P)	660	1215	210	H	26	4977	<b>1457</b>	H:Central Heating Only		
GRA146(S,P)	660	1415	210	H	26	5506	<b>1612</b>	H:Central Heating Only		
GRA176(S,P)	660	1715	210	H	26	6302	<b>1845</b>	H:Central Heating Only		
GRA206(S,P)	660	2030	210	H	26	7135	<b>2089</b>	H:Central Heating Only		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)





