

# HONEYCOMB



**MAX.WORKING PRESSURE 10 Bar**

**MAX.WORKING TEMPERATURE 95°C**

**OPEN/CLOSED HEATING SYSTEM O-C**

**MATERIAL STAINLESS STEEL SS / MILD STEEL MS**

**MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS**

**R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / **TR Heated Towel Rail & Radiator****

**Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems**

**Finish S : Brushed Matt / P : Polished**

Model Name	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipes or Sections	Heat Output Delta T 50 C		E :Electric only		
							BTU	Watts	Choice of Elements Watts	Brushed Matt - S	Polished P
HON3(S,P)	580	550	40	H	3	18	666	<b>195</b>	H:Central Heating Only		
HON5(S,P)	840	785	40	H	5	30	1110	<b>325</b>	H:Central Heating Only		
HON7(S,P)	1120	785	40	H	7	42	1554	<b>455</b>	H:Central Heating Only		
HON9(S,P)	1400	785	40	H	9	63	1998	<b>585</b>	H:Central Heating Only		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



