

# KAPTAN



**MAX.WORKING PRESSURE 10 Bar**

**MAX.WORKING TEMPERATURE 95°C**

**OPEN/CLOSED HEATING SYSTEM O-C**

**MATERIAL STAINLESS STEEL SS**

**MOUNTING POSITION VERTICAL V**

**R Radiator** / RT Radiator & Heated Towel Rail / T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipes or Sections	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
KA18	1040	500	40	E/H/D	5	18	2388	<b>699</b>	300	400		
KA24	1400	500	40	E/H/D	7	24	3183	<b>932</b>	400	600		
KA30	1760	500	40	E/H/D	9	30	3979	<b>1165</b>	600	900		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



