

# KARNAK



**MAX.WORKING PRESSURE 10 Bar**  
**MAX.WORKING TEMPERATURE 95°C**  
**OPEN/CLOSED HEATING SYSTEM O-C**  
**MATERIAL STAINLESS STEEL SS**  
**MOUNTING POSITION VERTICAL V**  
**R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator**  
 Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems  
 Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel gaps	Pipes or Sections	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements	Watts	Brushed Matt - S	Polished P
5K10	1000	500	30	E/H/D	11	12	1091	<b>320</b>	300	300		
5K17	1700	500	30	E/H/D	19	20	1766	<b>518</b>	400	600		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



