

PANACEA BATH



MAX.WORKING PRESSURE 8 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS

MOUNTING POSITION VERTICAL V

R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Option E/H/D	Towel Gaps	Pipes Or Sections	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
PANB704	660	400	75	E/H/D	1	11	1104	323	300			
PANB1004	985	400	75	E/H/D	2	16	1596	467	300			
PANB1204	1175	400	75	E/H/D	3	18	1813	531	400			
PANB1504	1500	400	75	E/H/D	4	22	2229	653	400			
PANB1704	1680	400	75	E/H/D	4	26	2594	759	400			
PANB705	660	500	75	E/H/D	1	11	1298	380	400			
PANB1005	985	500	75	E/H/D	2	16	1878	550	400			
PANB1205	1175	500	75	E/H/D	3	18	2131	624	400			
PAB1505	1500	500	75	E/H/D	4	22	2617	766	600			
PANB1705	1680	500	75	E/H/D	4	26	3053	894	600			
PANB706	660	600	75	E/H/D	1	11	1493	437	400	600		
PANB1006	985	600	75	E/H/D	2	16	2161	633	400	600		
PANB1206	1175	600	75	E/H/D	3	18	2449	717	600			
PAB1506	1500	600	75	E/H/D	4	22	3006	880	600	900		
PANB1706	1680	600	75	E/H/D	4	26	3512	1028	600	900		
PANB708	660	800	75	E/H/D	1	11	1881	551	400			
PANB1008	985	800	75	E/H/D	2	16	2726	798	400			
PANB1208	1175	800	75	E/H/D	3	18	3085	903	600			
PANB1508	1500	800	75	E/H/D	4	22	3783	1108	600	900		
PANB1708	1680	800	75	E/H/D	4	26	4431	1297	600	900		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

