

SEREN



MAX.WORKING PRESSURE 10 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS / MILD STEEL MS

MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS

Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	To Ga	Pip Or Sec	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
SE75	750	550	32	E/H/D	1	14	1599	468	300	400		
SE76	750	650	32	E/H/D	1	14	1817	532	300	400		
SE105	1000	550	32	E/H/D	2	18	2271	665	400	600		
SE135	1300	550	32	E/H/D	2	22	2439	714	400	600		
SE136	1300	650	32	E/H/D	2	22	2862	838	400	600		
SE175	1750	550	32	E/H/D	3	30	3651	1069	600	900		
SE176	1750	650	32	E/H/D	3	30	4266	1249	600	900		
SE75C	750	550	32	E/H/D	1	14	1599	468	300	400		
SE76C	750	650	32	E/H/D	1	14	1817	532	300	400		
SE105C	1000	550	32	E/H/D	2	18	2271	665	400	600		
SE135C	1300	550	32	E/H/D	2	22	2439	714	400	600		
SE136C	1300	650	32	E/H/D	2	22	2862	838	400	600		
SE175C	1750	550	32	E/H/D	3	30	3651	1069	600	900		
SE176C	1750	650	32	E/H/D	3	30	4266	1249	600	900		
SE75G	750	550	32	E/H/D	1	14	1599	468	300	400		
SE76G	750	650	32	E/H/D	1	14	1817	532	300	400		
SE105G	1000	550	32	E/H/D	2	18	2271	665	400	600		
SE135G	1300	550	32	E/H/D	2	22	2439	714	400	600		
SE136G	1300	650	32	E/H/D	2	22	2862	838	400	600		
SE175G	1750	550	32	E/H/D	3	30	3651	1069	600	900		
SE176G	1750	650	32	E/H/D	3	30	4266	1249	600	900		



We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)