

# SERHAD



**MAX.WORKING PRESSURE 10 Bar**  
**MAX.WORKING TEMPERATURE 95°C**  
**OPEN/CLOSED HEATING SYSTEM O-C**  
**MATERIAL STAINLESS STEEL SS**  
**MOUNTING POSITION VERTICAL V**

**R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator**

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

| Model Name (+S or P) | Height mm | Length mm | Depth mm | Fuel Options E/H/D | Towel Gaps | Pipes Or Sections | Heat Output Delta T 50 C |            | E :Electric only         |     | Price EURO       |            |
|----------------------|-----------|-----------|----------|--------------------|------------|-------------------|--------------------------|------------|--------------------------|-----|------------------|------------|
|                      |           |           |          |                    |            |                   | BTU                      | Watts      | Choice of Elements Watts |     | Brushed Matt - S | Polished P |
| SRD75                | 750       | 580       | 40       | E/H/D              | 1          | 14                | 1592                     | <b>466</b> | 300                      | 400 |                  |            |
| SRDE76               | 750       | 680       | 40       | E/H/D              | 1          | 14                | 1718                     | <b>503</b> | 300                      | 400 |                  |            |
| SRD105               | 1000      | 580       | 40       | E/H/D              | 2          | 18                | 2036                     | <b>596</b> | 400                      | 600 |                  |            |
| SRD106               | 1000      | 680       | 40       | E/H/D              | 2          | 18                | 2145                     | <b>628</b> | 400                      | 600 |                  |            |
| SRD155               | 1500      | 580       | 40       | E/H/D              | 3          | 28                | 3299                     | <b>966</b> | 600                      | 900 |                  |            |
| SRD156               | 1500      | 680       | 40       | E/H/D              | 3          | 28                | 3392                     | <b>993</b> | 600                      | 900 |                  |            |

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



