

STANZA



MAX.WORKING PRESSURE 10 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS / MILD STEEL MS

MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS

R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Pipes Or Section	Heat Output Delta T 50 C		E :Electric only			
						BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
STA15(S,P)	1510	260	260	E/H/D	8	6662	1950	8x200			
STA18(S,P)	1810	260	260	E/H/D	8	7994	2340	8x200	8x300		
STA20(S,P)	2010	260	260	E/H/D	8	8883	2601	8x300	8x400		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

