

TARDIS



MAX.WORKING PRESSURE 8 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C (**TAV1820(S)**)

OPEN/CLOSED HEATING SYSTEM C (**TAT1820**)

MATERIAL STAINLESS STEEL SS (**TAV1820(S)**) / MILD STEEL MS (**TAT1820**)

MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS

R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

| Model Name | Height mm | Length mm | Depth mm | Fuel Options E/H/D | Pipes or Sections | Heat Output Delta T 50 C | | E :Electric only | | |
|------------|-----------|-----------|----------|--------------------|-------------------|--------------------------|-------------|--------------------------|------------------|------------------------------|
| | | | | | | BTU | Watts | Choice of Elements Watts | Brushed Matt - S | Nickel,Stone, Aluminium etc. |
| TAV1820(S) | 1820 | 515 | 90 | E/H/D | 20 | 9290 | 2720 | 400 | | |
| TAT1820 | 1820 | 515 | 90 | E/H/D | 20 | 9156 | 2681 | 400 | | |

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

