

# TUBO



**MAX.WORKING PRESSURE 10 Bar**

**MAX.WORKING TEMPERATURE 95°C**

**OPEN/CLOSED HEATING SYSTEM O-C**

**MATERIAL STAINLESS STEEL SS / MILD STEEL MS**

**MOUNTING POSITION VERTICAL V/ HORIZONTAL H / FREESTANDING FS**

**R Radiator/ RT Radiator & Heated Towel Rail/ T Heated Towel Rail / TR Heated Towel Rail & Radiator**

**Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems**

**Finish S : Brushed Matt / P : Polished**

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipes Or Sections	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
TUB506	705	500	60	E/H/D	2	12	1496	<b>438</b>		300		
TUB508	990	500	60	E/H/D	3	16	1994	<b>584</b>		400		
TUB510	1275	500	60	E/H/D	4	20	2493	<b>730</b>		400		
TUB512	1560	500	60	E/H/D	5	24	2992	<b>876</b>		2X340		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



