

TUDOR



MAX.WORKING PRESSURE 10 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS

MOUNTING POSITION VERTICAL V

R Radiator / RT Radiator & Heated Towel Rail / T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipes Or Sections	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
TDR408	800	420	100	E/H/D	2	3	642	188	400			
TDR412	1200	420	100	E/H/D	3	4	857	251	600			
TDR508	800	520	100	E/H/D	2	3	693	203	400			
TDR512	1200	520	100	E/H/D	3	4	926	271	400	600		
TDR608	800	620	100	E/H/D	2	3	748	219	400	600		
TDR612	1200	620	100	E/H/D	3	4	1001	293	400	600		

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



