

WINDSOR



MAX.WORKING PRESSURE 8 Bar

MAX.WORKING TEMPERATURE 95°C

OPEN/CLOSED HEATING SYSTEM O-C

MATERIAL STAINLESS STEEL SS

MOUNTING POSITION VERTICAL V

R Radiator / RT Radiator & Heated Towel Rail / T Heated Towel Rail / TR Heated Towel Rail & Radiator

Fuel Options (E/H/D) – Electric only/ Hot water systems/ Dual fuel systems

Finish S : Brushed Matt / P : Polished

Model Name (+S or P)	Height mm	Length mm	Depth mm	Fuel Options E/H/D	Towel Gaps	Pipes Or Sections	Heat Output Delta T 50 C		E :Electric only		Price EURO	
							BTU	Watts	Choice of Elements Watts		Brushed Matt - S	Polished P
WIN5W8	798	493	50	E/H/D	2	14	1288	377	300	400		
WIN5W11	1150	493	50	E/H/D	3	20	1837	538	400			
WIN5W16	1612	493	50	E/H/D	4	31	2705	792	400	600		
WINE			Pair									

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of « T » piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)



